

350W Single Output Switching Power Supply

- AC input range selected by switch
- Protections:
short circuit/ over load/ over temp
- Forced air cooling by Build-in DC fan
- Cooling fan ON/OFF auto control
- Fix switching frequency at 25KHz
- Compact size, light weight
- Low cost
- 1 year warranty



CASE: 912A

215x115x50 mm

AC input voltage range.....	90~132VAC/ 180~264VAC selected by switch.
AC Inrush current.....	cold start, 25A/ 115V, 50A/ 230V
DC adjust range.....	±10% of rated output voltage
Over load protection.....	105%~135% fold back current limiting, auto recovery
Set, rise, hold up time.....	200ms, 50ms, 20ms at full load and 230VAC
Withstand voltage.....	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC for 1minute
Working temperature.....	-10-50°C (refer to output derating curve)
Safety standards.....	design refer to UL 1950
EMC standards.....	design refer to FCC part 15 J class B
Connection.....	9P/ 9.5mm pitch terminal block with cover
Weight/ packing	1.15kgs/pcs; 12pcs/ 15kgs/ 1CUFT

Stock No	Type No	Output	Tol.	R&N	Effi.	P.P.
10421	S-350-5	5V, 0~50.0A	±2%	150mV	73%	95
10422	S-350-7.5	7.5V, 0~40.0A	±2%	150mV	76%	95
10423	S-350-12	12V, 0~29.0A	±1%	150mV	79%	95
10424	S-350-13.5	13.5V, 0~25.8A	±1%	150mV	79%	95
10425	S-350-15	15V, 0~23.2A	±1%	150mV	80%	95
10426	S-350-24	24V, 0~14.6A	±1%	150mV	81%	95
10427	S-350-27	27V, 0~13.0A	±1%	200mV	82%	95
10428	S-350-48	48V, 0~7.30A	±1%	240mV	83%	95