

2KW Single Output with Parallel Function

- AC input 200~260VAC, 3 ϕ 3wires
- Protections: short circuit/ over voltage/over load/ over temp.
- High reliability; Low ripple noise
- Built-in remote sense function
- Built-in remote ON-OFF control
- With parallel function
- Can adjust from 20~100% output voltage by external control 1-5V
- Forced air cooling by built-in DC fan
- Case coating with paint
- 2 years warranty



320x212x134 mm

AC Input voltage range.....	200~260VAC, 3 ϕ 3wires, standard
AC Input current.....	10 A for@230VAC; 1 ϕ
DC adjust range.....	$\pm 5\%$ of rated output voltage
Load regulation.....	$\pm 2\%$ from 0~100% load
Over load protection.....	110~135%, shutoff, AC recycle to re-start
Over voltage protection.....	120~145% of rated output voltage
Working temperature.....	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C @100%, 60 $^{\circ}$ C @70% load
Withstand voltage.....	I/P-O/P, I/P-FG: 1500VAC for 1 minute
Safety standards.....	design refer to UL 1950, IEC950
Weight/ packing.....	9.0 kgs/pcs; 1pcs/ 10kgs/ CTN

Stock No	Type No	Output	Tol.	R&N	Eff.	P.P.
11081	SCN-2K0-05	5V, 0~250A	$\pm 3\%$	150mV	78%	1,825
11082	SCN-2K0-12	12V, 0~167A	$\pm 2\%$	150mV	84%	1,825
11083	SCN-2K0-15	15V, 0~134A	$\pm 2\%$	150mV	84%	1,825
11084	SCN-2K0-24	24V, 0~83.5A	$\pm 1\%$	240mV	85%	1,825
11085	SCN-2K0-48	48V, 0~42.0A	$\pm 1\%$	480mV	86%	1,825