

2K4W Parallel Type with PFC Function

- AC input 180~260VAC input
- Protections: short circuit/ over voltage/over load/ over temp.
- Built-in remote sense function
- Built-in remote ON-OFF control
- Power failure signal output
- With parallel function(N+1)
- Can adjust from 10~100% output voltage by external control 1-5V
- Forced air cooling by built-in DC fan
- 2 years warranty



320x212x124 mm

AC Input voltage range.....	180~260VAC, 47~63Hz
AC Input current.....	13.5 A for@230VAC
DC adjust range.....	±5% of rated output voltage
Load regulation.....	±1% from 0~100% load
Over load protection.....	current limiting, delay shutdown
Over voltage protection.....	110~135% of rated output voltage
Working temperature.....	-10°C ~+50°C @100%, 65°C @50% load
Withstand voltage.....	I/P-O/P, I/P-FG: 3750VAC for 1 minute.
Safety standards.....	design refer to UL1950, IEC60950
EMC standards.....	design refer to EN55022 classA
Weight/ packing.....	9.0kgs/pcs; 1pcs/ 10kgs/ CTN

Stock No	Type No	Output	Tol.	R&N	Eff.	P.P.
11121	SCP-2K4-12	12V, 0~200A	±1%	120mV	84%	2,300
11122	SCP-2K4-15	15V, 0~160A	±1%	150mV	85%	2,300
11123	SCP-2K4-24	24V, 0~100A	±1%	240mV	88%	2,300
11124	SCP-2K4-48	48V, 0~50.0A	±1%	480mV	89%	2,300