

Universal LED drivers constant current  
and constant voltage. 220-240Vac  
primary.

Senses and automatically sets the correct  
type of current or voltage to the load.  
short circuits, overload and overheating  
protection.

## UNIVERSAL LED DRIVERS CONSTANT CURRENT 350 and 700mA and CONSTANT VOLTAGE 12 and 24v

6W



LED Universal driver  
6W, 350mA, 24Vdc  
6W, 700mA, 12Vdc



LED Universal driver  
6W, 700mA, 12Vdc  
6W, 350mA, 24Vdc

## UNIVERSAL LED DRIVERS 6W

Power	0,5-6W	0,5-6W	0,5-6W
<b>Designation</b>	SLT6-700 IP	SLT6-350 IL	SLT6-700 IL
<b>Voltage primary (Vac)</b>	220-240Vac	220-240Vac	220-240Vac
<b>Voltage secondary (Vdc)</b>	12Vdc	24Vdc	12Vdc
<b>Current secondary (mA)</b>	700mA	350mA	700mA
<b>Load (W)</b>	0,5-6W	0,5-6W	0,5-6W
<b>Ambient temp. max. (Ta)</b>	+50°C	+50°C	+50°C
<b>Test temp. (Tc)</b>	+80°C	+70°C	+85°C
<b>Dimensions (LxBxH mm)</b>	57x44x25	67x34x20	67x34x20
<b>Weight (g)</b>	93	34	34
<b>Cover: Non-combustible thermaplastic</b>	Yes	Yes	Yes
<b>Colour</b>	White	White	White
<b>Protection against</b>			
-short-circuiting autom. rest	Yes	Yes	Yes
-overload -"-	Yes	Yes	Yes
-overheating -"-	Yes	Yes	Yes
<b>Softstart</b>	Yes	Yes	Yes
<b>Connections</b>			
-primary	Plug	Screwterm	Screwterm
-primary screwterm. area		0,75mm <sup>2</sup>	0,75mm <sup>2</sup>
-secondary	1,5m cable	Screwterm	Screwterm
-sec. screwterm. area		0,75mm <sup>2</sup>	0,75mm <sup>2</sup>
<b>Dimring with external PWM dimmer</b>	Yes	Yes	Yes
<b>Applications</b>			
-for built-in use in	Yes	Yes	Yes
-for independent use	Yes	Yes	Yes
-approved for mounting on furniture	Yes	Yes	Yes
<b>Isolation class</b>	II	II	II
<b>Protection index</b>	IP20	IP20	IP20
<b>Approvals</b>	CE	CE	CE
<b>EMC-requierments</b>	Approved	Approved	Approved