

Electronic Box LED driver for mounting in junction-box. 220-240Vac primary. Short circuit, overload and overheating protection.

BOX LED DRIVER CONSTANT VOLTAGE 12Vdc 6W



6W, 12Vdc

Vadsbo Transformatorer ab
Aröds Industriväg 34
SE-422 43 Hisings Backa
Sweden

Phone +46-31-235600
Fax +46-31-226010
E-mail info@vadsbo.net
Web www.vadsbo.net

VADSBO

BOX LED DRIVER CONSTANT VOLTAGE

Power	6W
Art. Nr.	V-3600612R
Voltage primary (Vac)	220-240
Voltage secondary (Vdc)	12
Current secondary (mA)	500
Load (W)	0-6W
Ambient temperature max (ta)	+50 °C
Test temperature (tc)	+75°C
Dimensions (LxWxH mm)	57x18
Weight	65g
Colour	Black
Isolation class	II
Protection index	IP20
Cover: Non-combustible thermoplastic	Yes
Protection against	
overload, automatic reset	Yes
overheating -"-	Yes
Softstart	Yes
EMC-requierments	Approved
Manufacturing standards	EN 61347-1 EN 61347-2-2 EN 61347-2-13 EN 61547 EN 55015 EN 61000-3-2 DIN VDE 0710T14 EN 61100-3-3
Approvals double	CE
Connections	
- primary: dubbel insulated 2 cable	Appr. 25cm
- secondary: connectivity simple insulated cable	Appr. 2x20cm
Dimming: External PWM dimmer	Yes
Applications	
- for built-in use in	Yes
- for independent use	Yes
- approved for mounting on furniture	Yes