

LIGHT-KEY

for dimmable low-power lamps

Save time and money with the right proven combination of:

Dimmers



Drivers



Dimmable Light Sources




Rating Explanation:

- 5) Excellent combination
- 4) The light source is dimmed in a good way
- 3) The light source is dimmed.
- Flicker / hum may appear in the bottom position
- 2) The light source is dimmed.
- Flicker / hum may appear in different positions
- 1) See 2) Too short-ranged dimming
- 0) Improper combination



P T = Push button dimmer trailing edge
P L = Push button dimmer leading edge
R T = Rotary knob dimmer trailing edge



Dimmer Type Effekt (W)

LD 220 P T 1-200

DU 250 P T 20-250

DRS 315 P T 50-315

DRS 420 P T 50-420

RHW 550 P L 50-550

ED 350 R T 50-350

KED 600A R T 35-600

	Effects	Mark	EAN-number	V-4022010IB	V-4025020IB	V-4031510IB	V-4042010IB	V-4055010IB	V-4035020TR	V-4060020TR
	3 W	LED L-ljus (GU10 base)	7332199052458	4,2	4,3	4,7	3,7	2,1	3,7	5
	4 W	LED Vadsbo (GU10 base)	7350030773546	5	2	3	0	0	3,5	5
	6 W	LED Philips	8727900900484	5	4,5	4,7	5	4	4,5	4,5
	7 W	LED Philips (GU10 base)	8727900867725 8727900860351	5	5	4,5	4,8	3,5	4,5	5
	8 W	LED Philips	8727900900484	5	5	4,7	5	4	4,5	4,8
	12 W	LED Osram	4008321965165	5	0	0	0	0	4,1	5
	8 W	CCFL Vadsbo	7350030773522	5	4	4	4	4,5	5	5
	9 W	CFL Megaman (E14 base)	4892657008692	4,8	4,5	2,6	3,8	2,5	3,7	4,5
	11 W	CFL Megaman (GU10 base)	4892657006971	4,7	4,3	3,8	4,2	2,7	4,5	4,3
	11 W	CFL Megaman	4892657007305	3,1	0	4,3	5	0	3,5	5
	12 W	CFL Philips	8727900825183	4,2	4	2,5	3,7	2,5	4,2	4
	15 W	CFL Megaman	4892657008111	4,4	4,2	4,3	4,5	3,5	3,7	4,3
	15 W	CFL Vadsbo	7350030773508	5	4	4,5	4,5	5	5	5
	15 W	CFL Narva	091171580027	3,3	3,5	3,2	3,5	2,5	3,3	3,5
	15 W	CFL Osram	4008321924209	4,4	3,9	2,4	3,3	2,3	3	3,3
	18 W	CFL Megaman	4892657006391	4,4	4	3,8	4,8	3,5	4	4,3
	20 W	CFL Philips	4008321924209	5	3,2	4,5	4,5	3,5	3,6	4,3
	20 W	CFL Sylvania	5410288248349	4,2	2,7	2,7	3,7	3	3,7	3,3
	20 W	CFL Govena	5906160706095	4,6	3	2,5	3,7	2,5	3,3	3,2
	20 W	CFL Osram	4008321080370	3,7	3,3	2,7	3,2	2,5	2,8	3,2
	20 W	CFL Vadsbo	7350030773515	5	4	4,5	4,5	5	5	5
	25 W	CFL Vadsbo	7350030773539	5	4	4,5	4,5	5	5	5

Black = Scores with only the lamp power load
Red = Scores where the base load is used to exceed the dimmers min. load

With E27 base unless other sockets are indicated
We reserve the right to make technical changes.

NOTE:

Depending on the brand, the LED and low-energy light bulbs consume up to twice the rated power (reactive power).

VADSBO



Vadsbo Transformatorer ab,
Aröds Industriväg 34
SE-422 43 Hisings Backa, Sweden
Phone +46 31 235600
E-mail: info@vadsbo.net

Fax +46 31 226010
Web www.vadsbo.net